

UNITED STATES PATENT APPLICATION
FOR
TIE-DOWN SYSTEM AND METHOD

Inventor:

Michael A. Wise

Prepared by:

Milord Keshishzadeh, Esq.
Milord & Associates, APC
2029 Century Park East
Suite 1700
Los Angeles, CA 90067
Telephone (310) 203-0989
Facsimile (310) 203-0986

EXPRESS MAIL CERTIFICATE OF MAILING


"Express Mail" mailing label number: EE506246592 US

Date of Deposit: August 10, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under CFR 1.10 on the date indicated above and is addressed to the "Assistant Commissioner of Patents, Box Patent Application, Washington DC 20231."

MILORD KESHISHZADEH

Name of person mailing paper or fee


Signature of person mailing paper or fee

TIE-DOWN SYSTEM AND METHOD

FIELD OF THE INVENTION:

5 This invention relates to the construction industry, and particularly to a device and method for securing a roof system to walls of a building in a steadfast manner.

BACKGROUND OF THE INVENTION:

10 In the construction of wooden frames for buildings, coupling and/or fastening devices are often used to join, or secure together, different frame members. One such junction includes securing a truss assembly to a wall framing or system. The truss assembly usually consists of a horizontal member attached to an inclined member, and this assembly is mounted to the wall system. Additionally, the inclined member may be attached directly to the wall system. In either
15 case, the security of the truss to the wall system may be compromised as a result of the attachment of the inclined member to the truss or wall system. Couplings may be used to secure the trusses to the wall systems. These couplings must be durable enough to resist shear and tension loads, but simple in construction for easy, on-the-job installation.

20 A particular problem in climatic regions subject to severe winds is the shearing off of the roof assembly from the wall assembly during high wind storms or hurricanes. Government regulations and standards for manufactured homes for use in regions subject to hurricanes now require all roof trusses to be tied directly to the wall studs by enhanced means. Therefore, some

means for directly tying the truss assembly to the wall studs is needed.

In the past, relatively complicated couplings have been developed to mount the truss assembly to the wall. Examples of such known assemblies are seen in U.S. Pat. No. 5,561,949 issued October 8, 1996 to Knoth; U.S. Pat. No. 4,932,173 issued June 12, 1990 to Commins; U.S. Pat. No. 5,560,156 issued October 1, 1996 to McDonald; U.S. Pat. No. 5,732,524 issued March 31, 1998 to Kalker, Jr. et al.; and U.S. Pat. No. 6,094,880 issued August 1, 2000 to Thompson.

One problem which each of the known couplings suffer from is that they are not easily adapted to function with poured concrete walls in which modular wall preforms, each comprising a pair of high-density foam panels which are maintained in a parallel-spaced relationship by a series of bridging "webs" extending between and through and molded into the panels, are interlockingly stacked together to define a concrete form for the poured concrete wall. With reinforcing steel bars optionally suspended within the assembled wall form, preferably through use of hooks or other retainers provided on each bridging web, the concrete is thereafter poured between the panels to complete the wall.

The prior art does not address the need for a more effective method and device for creating securing roof systems to wall systems, and in particular to preform walls having a curable material therein. Therefore, there remains a long standing and continuing need for an advance in the art of tie-down systems that is simpler in both design and use, is more

economical, efficient in its construction and use, and is adapted to affix the roof system to the wall system in a steadfast manner.

SUMMARY OF THE INVENTION:

5

Accordingly, it is a general object of the present invention to overcome the disadvantages of the prior art.

10
15

In particular, it is an object of the present invention to provide a tie down system that is simple and inexpensive to manufacture.

It is another object of the invention to provide a tie-down system that is easy to install during construction.

It is another object of the invention to provide a tie-down system that is capable of withstanding large wind shear forces.

20 In keeping with the principles of the present invention, a unique tie-down system is disclosed having a first member that is adapted to receive trusses therein and attach the same to the wall of a building in a steadfast manner. In addition, a second member is herein disclosed that is adapted to attach the gable end trusses of a roof system to the wall system at predetermined spaces in a steadfast manner.

Such stated objects and advantages of the invention are only examples and should not be construed as limiting the present invention. These and other objects, features, aspects, and advantages of the invention herein will become more apparent from the following detailed description of the embodiments of the invention when taken in conjunction with the

5 accompanying drawings and the claims that follow.

BRIEF DESCRIPTION OF THE DRAWINGS:

It is to be understood that the drawings are to be used for the purposes of illustration only

10 and not as a definition of the limits of the invention.

In the drawings, wherein similar reference characters denote similar elements throughout the several views:

15 **Figure 1** is a perspective view of a first member of a tie down system adapted to receive a member therein.

Figure 2 is a perspective view of a second member of a tie down system adapted to receive a member therein.

20 **Figure 3** is a top plan view of a first member of a tie down system in an unassembled form.

Figure 4 is a top plan view of a second member of a tie down system in an unassembled form..

Figure 5 is a perspective partial cutaway view of a first member receiving a member
5 therein and attaching the same to a wall system.

Figure 6 is a perspective partial cutaway view of a plurality of second members illustrating the attachment thereof to a member and anchoring of the structure to a wall system.

DETAILED DESCRIPTION OF THE INVENTION:

Referring to Figures 1 and 2, a first member 10 and a second member 12 comprise a roof
tie down system. Although in a preferred embodiment first member 10 and second member 12
are used in combination for the tie down system, it is to be understood that first member 10 or
5 second member 12 can be modified and used independent of the other.

First member 10 has a bottom panel 14 and bottom panel has a first extended region 16
and a second extended region 18 that extending in opposing directions from one another.

Although first extended region 16 and second extended region 18 are illustrated in one preferred
20 embodiment as not being in linear alignment, it is to be understood that first extended region 16
and second extended region 18 may be adapted to be in linear alignment while maintaining
bottom panel 14 therebetween. A first panel 20 extends in a vertical direction and is attached to
bottom panel 14 and is in proximity to first extended region 16. A second panel 22 extends in a

vertical direction and is attached to bottom panel 14 and is in proximity to second extended region 18. A guide 24 is defined by bottom panel 14, first panel 20, and second panel 22. A first aperture 26 is defined through first extended region 16 and a second aperture 28 is defined through second extended region 28.

5

Now also referring to Figure 3, one preferred method of constructing first member 10 is set forth. It is to be understood that although a unitary method of construction of first member 10 is herein illustrated in one preferred embodiment, first member 10 may be constructed from several disjointed elements in alternate preferred embodiments. In addition, although several preferred dimensions or shapes may be assigned to first member 10 in a preferred embodiment, it is to be understood that alternate sizes and shapes are also contemplated hereby. First member 10 may be cut out from a unitary piece of material such that first panel 20 and second panel are in a similar plane as bottom panel 14, first extended region 16, and second extended region 18. A first slit 30 is cut between first panel 20 and first extended region 16 such that first panel 20 may be manipulated into a vertical alignment in relation to first extended region 16 and bottom panel 14. A second slit 32 is cut between second panel 22 and first extended region 18 such that second panel 22 may be manipulated into a vertical alignment in relation to second extended region 28 and bottom panel 14. By varying the length of slits 30 and 32, the width of bottom panel 14 and, in turn, guide 24 may be varied accordingly.

20

Now referring to Figure 2 in particular, second member 12 has a bottom plate 34 with an extended section 36 extending therefrom in a substantially similar plane. Bottom plate 34 has a first edge 38 and a second edge 40, and a top edge 42 at a point distal to extended section 36. A

first plate 43 extends from top edge 42 of bottom plate 34 in a substantially vertical manner. However, in an alternate embodiment, first plate 43 is omitted and does not affect the functioning of second member 12.

5 Extended section 36 has a first border 44 and a second border 46 which are interconnected by a third border 48, such that third border 48 is distal to bottom plate 34. A first sheet 50 arises from first border 44 of extended section 36 in a vertical direction and extends for a substantial length thereof. A second sheet 52 arises from second border 46 of extended section 36 in a vertical direction and extends for a substantial length thereof. First sheet 50 has a first front border 54 and second sheet 52 has a second front border 56. A third sheet 58 extends from first front border 54 in a substantially perpendicular manner and a fourth sheet 60 extends from second front border 56 in a substantially perpendicular manner in relation to first sheet 50 and second sheet 52 respectively. A first channel 62 is defined by first plate 43, bottom plate 34, third sheet 58, and fourth sheet 60. In addition, at least a hole 64 is defined through extended section 36 with predetermined dimensions.

10 Now also referring to Figure 4, one preferred method of constructing second member 12 is set forth. It is to be understood that although a unitary method of construction of second member 12 is herein illustrated in one preferred embodiment, second member 12 may be
20 constructed from several disjointed elements in alternate preferred embodiments. In addition, although several preferred dimensions or shapes may be assigned to second member 12 in a preferred embodiment, it is to be understood that alternate sizes and shapes are also contemplated hereby. Second member 12 may be cut out from a unitary piece of material such

that first plate 43, first sheet 50, second sheet 52, third sheet 58, and fourth sheet 60 are in a similar plane as bottom plate 34 and extended section 36. A third slit 66 is cut between third sheet 58 and bottom plate 34 such that first sheet 50 may be manipulated along first border 44 to be in vertical alignment in relation to extended section 36 and bottom plate 34. A fourth slit 68 is cut between fourth sheet 60 and bottom plate 34 such that second sheet 52 may be manipulated along second border 46 to be in vertical alignment in relation to extended section 36 and bottom plate 34. In an alternate preferred embodiment, a fifth slit 70 and a sixth slit 72 are cut into first plate 43 in a perpendicular direction to top edge 42 such that a first flap 74, a second flap 76, and a third flap 78 are created. At least one of flaps 74, 76, or 78 may remain in a horizontal plane while at least one of flaps 74, 76, or 78 are manipulated along the top edge 42 axis to be in vertical relation to bottom plate 34. The length of the slits 70 and 72 determines the length of flaps 74, 76, and 78, and the horizontally aligned flap may be utilized to set second member 12 a specified distance from a structure and also for alignment of second member 12.

Now referring to Figure 5, first member 10 is illustrated enclosing a member 80 and attaching member 80 to a structure 82. Although a preform wall is illustrated as structure 82, it is to be understood that first member 10 may also be used with other wall structures such as, but not limited to, wooden frame wall system.

Structure 82 is formed by pouring a suitable curable material 84, such as concrete, between a first wall 86 and a second wall 88. Structure 82 for purposes of illustration, but not limitation, may be obtained from AAB Building Supplies, Inc. of Ottawa, Canada, under the trademark BLUEMAXX® which uses a plurality of interlocking modular performs to construct a

structure 82 of desired length. After curable material 84 is poured between first wall 86 and second wall 88, a top surface 90 is created thereby. In one preferred embodiment, a plank 92 is attached to top surface 90. Plank 92 has a plurality of voids defined therethrough and corresponding with apertures 26 and 28 of first member 10. Before curable material 84 has
5 cured, an anchoring means 94 is inserted through each of apertures 26 and 28 and through the corresponding void in plank 92 and into the curable material 84, whereby upon curing thereof, anchoring means 94 is steadfastly held within curable material 84. Anchoring means 94 has an elongated portion 96 and a head portion 98, wherein elongated portion 96 is of sufficient diameter to pass through apertures 26 and 28 and head portion 98 is of sufficient diameter to
10 engage extended regions 16 and 18 and to fixedly anchor first member 10 to structure 82.

In one preferred embodiment, member 80 may be a truss which has a horizontal element 100 and an inclined element 102 attached by a truss clip 104 to form the frame for a building roof. After curable material 84 has cured, member 80 is lowered into guide 24 of first member
15 10 such that horizontal element 100 is flush with bottom panel 14. First panel 20 and second panel 22 are then attached to member 80 by at least an affixing means 106 such as, but not limited to, threaded elements or nails. A plurality of first members 10 may be placed along plank 92 at desired locations in order to attach a plurality of members 80 thereto as is customary in the art of roof building.

20
Now referring to Figure 6, second member 12 is illustrated enclosing member 80 and attaching member 80 to structure 82. Although a preform wall is illustrated as structure 82, it is to be understood that second member 12 may also be used with other wall structures such as, but

not limited to, wooden frame wall system. After curable material 84 is poured between first wall 86 and second wall 88, top surface 90 is similarly created thereby. In one preferred embodiment, plank 92 is attached to top surface 90, however it is to be understood that members 10 and 12 may be attached directly to curable material 84. Plank 92 has a plurality of voids defined therethrough and corresponding with holes 64 of second member 12. Before curable material 84 has cured, anchoring means 94 is inserted through each hole 64 and through the corresponding void in plank 90 and into the curable material 84, whereby upon curing thereof, anchoring means 94 is steadfastly held within curable material 84. Anchoring means 94 may have a textured elongated portion 96 to more fixedly attach the same to curable material 84. Elongated portion 96 is of sufficient diameter to pass through hole 64 and head portion 98 is of sufficient diameter to engage extended section 36 and to fixedly anchor second member 12 to structure 82. In one preferred embodiment, elongated portion 96 has at least a half-inch diameter and is of sufficient length such that at least seven inches of elongated portion 96 is maintained within curable material 84.

In one preferred embodiment, member 80 may be a gable end truss which has a horizontal element 100 and an inclined element 102 (not shown) attached by a truss clip 104 (not shown) and vertical members (not shown) which attach the horizontal element 100 to inclined element 102 at a plurality of locations. Gable end trusses are located on opposing walls and run along the top surface thereof such that the internal trusses are located therebetween. After curable material 84 has cured, member 80 is lowered into first channel 62 of second member 12 such that horizontal element 100 is flush with bottom plate 34. Third sheet 58 and fourth sheet 60 are then attached to horizontal element 100 by at least an affixing means 106 such as, but not

limited to, threaded elements or nails. A plurality of second members 12 may be placed along plank 92 at desired locations in order to engage horizontal member of the gable end truss at a plurality of locations as is customary in the art of roof building or required by the building code of the region.

5

Various materials may be used to construct first member 10 and second member 12, and for purposes of illustration, but not limitation, in one preferred embodiment members 10 and 12 are constructed of a metal or a metal alloy such as, but not limited to, steel or aluminum.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

While the above description contains many specificities, these should not be construed as limitations on the scope of the invention, but rather as an exemplification of preferred embodiments thereof. Many other variations are possible without departing from the essential spirit of this invention. Accordingly, the scope of the invention should be determined not by the embodiments illustrated, but by the appended claims and their legal equivalents.